



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B401BB  
**Voltage Class (kV):** 115      **BIL (kV):** 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	1600
115W1216AK (Amps)		1200	1600

**General Comments:**

**Replacement Information**

**ABB Style Number:** [115W1216AK](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B401BB	550kV	23 in.	23 in.	43 in.	49.9 in.	8.75 in.	13.25 in.	6	1.25 slots in.	86.18 in.
115W1216AK	550kV	23 in.	23 in.	42.963 in.	50.095 in.	7.725 in.	13.25 in.	6	1.25 in.	115.395 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B401BB	36.26 in.	9.625 in.	N/A	42.25 in.	1.5-12x2.125	none ansi fig2 or fig 3
115W1216AK	36.414 in	8 in.	N/A	40.164 in	1.500-12UN-2A, 2.125 USABLE THD, SP x 12 UN-2A	(8) .375-16 UN-2B on 3.75 BC (8) .500-13 UN-2B on 6.75 BC