



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 11B566BB

Voltage Class (kV): 115 **BIL (kV):** 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
115W1620XC (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: [115W1620XC](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B566BB	550kV	23 in.	23 in.	43 in.	55.75 in.	8.75 in.	13.25 in.	6	1.25 slots in.	103.9 in.
115W1620XC	550kV	23 in.	23 in.	42.984 in.	55.828 in.	8.75 in.	13.25 in.	6	1.25 in.	105.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B566BB	42.12 in.	9.63 in.	in.	48.12 in.	2-12x2.5 x 2.50	ansi/IEEE fig 2 or 3
115W1620XC	42.141 in.	9.625 in.	N/A	48.141 in.	2.0-12x3.25 usable x 12 UN-2A	(4) .375-16 on 3.750 BC, (8) .500-13 on 6.75 BC (8) .500-13 in.

Cable Adapter:

NONE

Flange Adapter:

NONE