



**Original Bushing Information**

Original Bushing Manufacturer: G.E.      Mounting Position:  
 Catalog Number: 11B568BB  
 Voltage Class (kV): 115      BIL (kV): 550

|                       |          |                  |                     |
|-----------------------|----------|------------------|---------------------|
| Application           | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) |          | 1600             | 2000                |
| 115W1620UL (Amps)     |          | 1600             | 2000                |

**General Comments:**

**Replacement Information**

ABB Style Number: [115W1620UL](#) Alternate ABB Style Number:

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

| Catalog Number | BIL   | EL     | CT     | L          | B          | D        | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep      |
|----------------|-------|--------|--------|------------|------------|----------|-------------|--------------|--------------------|------------|
| 11B568BB       | 550kV | 23 in. | 23 in. | 43 in.     | 49.88 in.  | 8.75 in. | 13.25 in.   | 6            | 1.25 slots in.     | 86.5 in.   |
| 115W1620UL     | 550kV | 23 in. | 23 in. | 42.984 in. | 49.891 in. | 8.75 in. | 13.25 in.   | 6            | 1.25 in.           | 87.688 in. |

| Catalog Number | Strike     | P Dia.    | Cable Height/Pin Height for AB Bushing - CH | LHV        | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration                              |
|----------------|------------|-----------|---|------------|-------------------------------|---|
| 11B568BB       | 36.25 in.  | 9.625 in. | N/A   | 42.25 in.  | 2-12x2.5                      | fig 3 per ansi  |
| 115W1620UL     | 36.266 in. | 9.625 in. | N/A   | 42.266 in. | 2.0-12x 3.250 x 12 UN-2A      | (4) .375-16 on 3.750 BC,(8) .500-13 on 6.75 BC<br>(8) .500-13 in. |

Cable Adapter:

NONE

Flange Adapter:

NONE