



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical

**Catalog Number:** 11B574BB

**Voltage Class (kV):** 115      **BIL (kV):** 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
115W1620XC (Amps)		1600	2000

**General Comments:**

**Replacement Information**

**ABB Style Number:** [115W1620XC](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B574BB	550kV	23 in.	23 in.	43 in.	55.81 in.	8.75 in.	13.25 in.	6	1.250 in.	N/A
115W1620XC	550kV	23 in.	23 in.	42.984 in.	55.828 in.	8.75 in.	13.25 in.	6	1.25 in.	105.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B574BB	42 in.	9.625 in.	N/A	48 in.	2-12x2.63	fig 3 per ansi/IEEE
115W1620XC	42.141 in.	9.625 in.	N/A	48.141 in.	2.0-12x3.25 usable x 12 UN-2A	(4) .375-16 on 3.750 BC,(8) .500-13 on 6.75 BC (8) .500-13 in.

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE