



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** Vertical  
**Catalog Number:** 11B583  
**Voltage Class (kV):** 115 **BIL (kV):** 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
115W1620XC (Amps)		1600	2000

**General Comments:** Type "U"

**Replacement Information**

**ABB Style Number:** [115W1620XC](#) **Alternate ABB Style Number:** [115X1620XC](#)

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Adjust line bus. (See B dimension)

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B583	550kV	23 in.	23 in.	43 in.	63.5 in.	8.75 in.	13.25 in.	6	1.25 in.	N/A
115W1620XC	550kV	23 in.	23 in.	42.984 in.	55.828 in.	8.75 in.	13.25 in.	6	1.25 in.	105.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B583	43.12 in.	9.625 in.	N/A	49.12 in.	2-12x2.63	ansi/IEEE fig 2 or 3
115W1620XC	42.141 in.	9.625 in.	N/A	48.141 in.	2.0-12x3.25 usable x 12 UN-2A	(4) .375-16 on 3.750 BC,(8) .500-13 on 6.75 BC (8) .500-13 in.

**Cable Adapter:** NONE

**Flange Adapter:** NONE