



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B593BB
Voltage Class (kV): 115 **BIL (kV):** 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
115W1620UL (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: 115W1620UL **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Note difference in "B" - external buss may need adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B593BB	550kV	23 in.	23 in.	43 in.	55.562 in.	8.75 in.	13.25 in.	6	1.25 slots in.	N/A
115W1620UL	550kV	23 in.	23 in.	42.984 in.	49.891 in.	8.75 in.	13.25 in.	6	1.25 in.	87.688 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B593BB	N/A	9.625 in.	N/A	41.18 in.	2-12x2.625	ansi fig 3
115W1620UL	36.266 in.	9.625 in.	N/A	42.266 in.	2.0-12x 3.250 x 12 UN-2A	(4) .375-16 on 3.750 BC,(8) .500-13 on 6.75 BC (8) .500-13 in.

Cable Adapter: NONE

Flange Adapter: NONE