



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B623
Voltage Class (kV): 138 **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
138X1620XC (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: [138X1620XC](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B623	650kV	23 in.	23 in.	46.75 in.	65.9 in.	9.75 in.	14.25 in.	6	1.25 slots in.	124.9 in.
138X1620XC	650kV	23 in.	23 in.	46.734 in.	65.907 in.	9.75 in.	14.25 in.	6	1.25 in.	124.9 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B623	50.88 in.	N/A	N/A	56.9 in.	2-12x2.5	ansi/IEEE FIG #2
138X1620XC	50.891 in.	9.500 in.	N/A	56.891 in.	2.0-12UNx2.5, SP x	IEEE fig.2&3 N/A

Cable Adapter:

NONE

Flange Adapter:

NONE