



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B623BB  
**Voltage Class (kV):** 138      **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
138W1620XC (Amps)		1600	2000

**General Comments:**

**Replacement Information**

**ABB Style Number:** [138W1620XC](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B623BB	650kV	23 in.	23 in.	46.75 in.	65.9 in.	9.75 in.	14.25 in.	6	1.25 slots in.	124.9 in.
138W1620XC	650kV	23 in.	23 in.	46.734 in.	65.969 in.	9.75 in.	14.25 in.	6	1.25 in.	124.9 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B623BB	50.88 in.	N/A	N/A	56.9 in.	2-12x2.5	ansi/IEEE FIG #2
138W1620XC	50.891 in.	9.500 in.	N/A	56.891 in.	2.000-12UN-2A, 3.25 USABLE THD SP x 12 UN-2A	IEEE fig.2&3 (8) .500 in.13 UN-2B

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE