



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 11B633BB

Voltage Class (kV): 138 **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	1600
138W1620XC (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: [138W1620XC](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B633BB	650kV	23 in.	23 in.	46.75 in.	66 in.	9.75 in.	14.25 in.	6	1.25 in.	N/A
138W1620XC	650kV	23 in.	23 in.	46.734 in.	65.969 in.	9.75 in.	14.25 in.	6	1.25 in.	124.9 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B633BB	50.88 in.	10.625 in.	N/A	56.88 in.	2-12 x 2.5	fig 3 per IEEE 24
138W1620XC	50.891 in.	9.500 in.	N/A	56.891 in.	2.000-12UN-2A, 3.25 USABLE THD SP x 12 UN-2A	IEEE fig.2&3 (8) .500 in.13 UN-2B

Cable Adapter:

NONE