



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:**  
**Catalog Number:** 11B650  
**Voltage Class (kV):** 161 **BIL (kV):** 750

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
161X2000UB (Amps)		2000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 161X2000UB **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B650	750kV	23 in.	23 in.	50.25 in.	73.47 in.	10.75 in.	15.75 in.	8	1.25 slots in.	136.5 in.
161X2000UB	750kV	N/A	23 in.	50.297 in.	75.493 in.	10.75 in.	15.75 in.	8	1.25 in.	131.938 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B650	50.25 in.	12.125 in.	N/A	56.25 in.	2.0-12 x 2.5	ansi/IEEE fig 2 or 3
161X2000UB	50.28 in.	12.125 in.	N/A	56.28 in.	2.0-12 x 2.625 USABLE, SP x	(4) .375-16 on 3.75 dia B.C., 750 Deep, (8) .500-13 on 6.75 dia B.C. ....