



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B551
 Voltage Class (kV): 115 BIL (kV): 550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	
115X1216AK (Amps)		1200	1600

General Comments:

Replacement Information

ABB Style Number: [115X1216AK](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B551	550kV	23 in.	23 in.	43 in.	49.9 in.	8.75 in.	13.25 in.	6	1.25 slots in.	N/A
115X1216AK	550kV	23 in.	23 in.	42.984 in.	49.907 in.	8.75 in.	13.25 in.	6	1.25 in.	86.188 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B551	N/A	N/A	N/A	N/A	1.5-12x2.125	none ansi fig 2 or fig 3
115X1216AK	36.266 in.	9.625 in.	N/A	42.266 in.	1.5-12UN-2A, 2.000 USABLE THD, SP x	(4) .375-16 on 3.750 BC,(8) .500-13 on 6.75 BC N/A

Cable Adapter:

NONE

Flange Adapter:

NONE