



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.    **Mounting Position:**  
**Catalog Number:** 11B660  
**Voltage Class (kV):** 138    **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
138X1620AC (Amps)		1600	2000

**General Comments:**

**Replacement Information**

**ABB Style Number:** 138X1620AC    **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B660	650kV	23 in.	23 in.	46.75 in.	55.75 in.	9.75 in.	14.25 in.	6	1.25 slots in.	103.9 in.
138X1620AC	650kV	23 in.	23 in.	46.734 in.	55.78 in.	9.75 in.	14.25 in.	6	1.25 in.	103.9 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B660	4.12 in.	10.625 in.	N/A	48.13 in.	2.0-12 X 2.50	ANSI/IEEE FIG 2
138X1620AC	42.141 in.	9.5 in.	N/A	48.141 in.	2.000-12UN-2A x 2.500 USEABLE THD x 12 UN-2A	(8) .500-13 in.