



**Original Bushing Information**

Original Bushing Manufacturer: G.E.      Mounting Position:  
 Catalog Number: 11B660BB  
 Voltage Class (kV): 138      BIL (kV): 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
138W1620AC (Amps)		1600	2000

**General Comments:**

**Replacement Information**

ABB Style Number: [138W1620AC](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B660BB	650kV	23 in.	23 in.	46.75 in.	55.75 in.	9.75 in.	14.25 in.	6	1.25 slots in.	103.9 in.
138W1620AC	650kV	23 in.	23 in.	46.734 in.	55.766 in.	9.75 in.	14.25 in.	6	1.25 in.	105.2 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B660BB	42.06 in.	10.625 in.	N/A	48.13 in.	2.0-12 X 2.50	ANSI/IEEE FIG 2
138W1620AC	42.141 in.	9.5 in.	N/A	48.141 in.	2.0-12x3.250 x 12 UN-2A	IEEE fig 2 & 3 (8) .500-13 in.

Cable Adapter:

NONE

Flange Adapter:

NONE