



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B686
Voltage Class (kV): 230 **BIL (kV):** 750

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
230W0800UK (Amps)	800		

General Comments:

Replacement Information

ABB Style Number: [230W0800UK](#) **Alternate ABB Style Number:** [230X0800UK](#)

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B686	750kV	23 in.	23 in.	50.688 in.	91.75 in.	10.75 in.	15.75 in.	8	1.25 in.	173 in.
230W0800UK	750kV	23 in.	23 in.	50.734 in.	92.047 in.	10.75 in.	15.75 in.	8	1.25 in.	178 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B686	64.625 in.	12.125 in.	81.625 in.	81.625 in.	1.5-12 x 2.125, SP	1.625 I/D Tube, (4) .375 - 16 x 3.75 BC
230W0800UK	64.594 in.	11.375 in.	81.955 in.	71.219 in.	1.5-12UN-2A, 2.125 USABLE THD, SP x 12 UN-2A	1.625 i.d. tube 1.625 in.I.D. Tube

Cable Adapter:

NONE