



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B687BB
Voltage Class (kV): 230 **BIL (kV):** 750

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
230W1600UL (Amps)		1600	

General Comments:

Replacement Information

ABB Style Number: [230W1600UL](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B687BB	750kV	23 in.	23 in.	50.3 in.	88.438 in.	10.75 in.	15.75 in.	8	1.25 solts in.	177.3 in.
230W1600UL	750kV	23 in.	23 in.	50.296 in.	90.739 in.	10.75 in.	15.75 in.	8	1.25 in.	178 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B687BB	64.63 in.	12.13 in.	N/A	71.25 in.	2.0-12 x 2.5	ANSI fig 2 & 3
230W1600UL	64.594 in.	11.375 in.	N/A	71.219 in.	2.0-12x2.5 USABLE, SP x 12 UN-2A	(8) .5-13 holes on 6.75 bc / (4) .375-16 holes on 3.75 bc (8) .500-13 in.