



**Original Bushing Information**

Original Bushing Manufacturer: G.E. Mounting Position:  
 Catalog Number: 11B718  
 Voltage Class (kV): 196 BIL (kV): 900

|                       |          |                  |                     |
|-----------------------|----------|------------------|---------------------|
| Application           | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | 800      |                  |                     |
| 196X0800AY (Amps)     | 800      |                  |                     |

General Comments: 800 Amp Draw Lead Access

**Replacement Information**

ABB Style Number: [196X0800AY](#) Alternate ABB Style Number:

**Review dimensional differences verifying critical dimensions to meet application requirements.**

Notes/Comments: Note: Cable Adapter Needed Note: For 800 Amp Draw Lead Application Only

| Catalog Number | BIL   | EL        | CT        | L          | B           | D        | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep   |
|----------------|-------|-----------|-----------|------------|-------------|----------|-------------|--------------|--------------------|---------|
| 11B718         | 900kV | 26.75 in. | 26.75 in. | 60 in.     | 104.19 in.  | 12.5 in. | 21 in.      | 12           | 1.25 slots in.     | N/A     |
| 196X0800AY     | 900kV | 26.75 in. | 26.75 in. | 60.046 in. | 106.032 in. | 12 in.   | 21 in.      | 12           | 1.25 in.           | 216 in. |

| Catalog Number | Strike     | P Dia.     | Cable Height/Pin Height for AB Bushing - CH | LHV        | Top Terminal Threads (inches)           | Bottom Terminal Thread/Configuration |
|----------------|------------|------------|---|------------|---|--------------------------------------|
| 11B718         | 79.31 in.  | N/A        | 91.44 in.                                   | 85.31 in.  | 1.5-12x2.125                            | fig 3 per IEEE 24                    |
| 196X0800AY     | 79.219 in. | 16.875 in. | 100.595 in.                                 | 85.297 in. | 1.5-12x2.0 USABLE Thread, SP x 12 UN-2A | 2.00 ID TUBE<br>2.000 in.I.D. Tube   |

Cable Adapter: 1ZUA264308-BAB

Flange Adapter: NONE