



**Original Bushing Information**

Original Bushing Manufacturer: G.E. Mounting Position:  
 Catalog Number: 11B745\*  
 Voltage Class (kV): 288 BIL (kV): 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
362W1600VC (Amps)		1600	

**General Comments:**

**Replacement Information**

ABB Style Number: 362W1600VC Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B745*	1300kV	27 in.	27 in.	71.25 in.	148.125 in.	20.125 in.	28 in.	12	2.25 holes in.	263.7 in.
362W1600VC	1300kV	27 in.	27 in.	71.219 in.	145.11 in.	20.125 in.	28 in.	12	2.25 in.	263.75 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B745*	102.12 in.	20 in.	133.00 in.	115.25 in.	2.25-12x2.25	0.5-13 tap (12) on 9in B.C.
362W1600VC	102.094 in.	20.000 in.	N/A	115.219 in.	2.250-12 x 2.125, SP x	(12) .500-13UN-2B, .875 DEEP, EQ SPACED AT 30 DEG, ON 9.000 DIA. B.C. N/A