



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B746BB
Voltage Class (kV): 345 **BIL (kV):** 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
362W0800VA (Amps)	800		

General Comments:

Replacement Information

ABB Style Number: [362W0800VA](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Cable Adapter Required Note Difference in "B" - External Buss May Need Adjusted

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B746BB	1300kV	27 in.	27 in.	71.88 in.	148.13 in.	20.12 in.	28 in.	12	2.25 in.	N/A
362W0800VA	1300kV	27 in.	27 in.	71.907 in.	152.061 in.	20.125 in.	28 in.	12	2.25 in.	263.75 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B746BB	102.12 in.	20 in.	131.00 in.	115.25 in.	1.125-12x2.125, SP	2.00 id tube, (12) 0.5-13 tap on 9in B.C.
362W0800VA	102.094 in.	20 in.	136.062 in.	115.219 in.	1.125-12 x 2.125, SP x	2.000 id tube, (12) .500-13 on 9.0 BC N/A

Cable Adapter: 1ZUA264308-BAA

Flange Adapter: NONE