



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B748BB
 Voltage Class (kV): 550 BIL (kV): 1550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000UD (Amps)		2000	

General Comments:

Replacement Information

ABB Style Number: 550W2000UD Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" - External Bus may need adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B748BB	1550kV	26.75 in.	26.75 in.	86.7 in.	190.08 in.	23 in.	31 in.	16	1.25 in.	290 in.
550W2000UD	1550kV	26.75 in.	26.75 in.	86.719 in.	208.312 in.	23 in.	31 in.	16	1.25 in.	463 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B748BB	157 in.	23 in.	N/A	160 in.	2-12x2.63	(4) 0.5-13x7 (4) 0.5-13x10.5
550W2000UD	170.031 in.	23 in.	N/A	177.531 in.	2.0-12x2.5 x 2.5	(4) .50-13 on 7.0 B.C., (4) .50-13 on 10.5 B.C. N/A

Cable Adapter: NONE

Flange Adapter: NONE