



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B776BB  
**Voltage Class (kV):** 550      **BIL (kV):** 1550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000UD (Amps)		2000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [550W2000UD](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B776BB	1550kV	26.75 in.	26.75 in.	86.7 in.	208.3 in.	22.7 in.	31 in.	16	1.25 holes in.	408.75 in.
550W2000UD	1550kV	26.75 in.	26.75 in.	86.719 in.	208.312 in.	23 in.	31 in.	16	1.25 in.	463 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B776BB	170 in.	23 in.	in.	178 in.	2.0-12 x 2.5	(4) 0.5-13x7 (4) 0.5-13x10.5
550W2000UD	170.031 in.	23 in.	N/A	177.531 in.	2.0-12x2.5 x 2.5	(4) .50-13 on 7.0 B.C., (4) .50-13 on 10.5 B.C. N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE