



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B803
 Voltage Class (kV): 196 BIL (kV): 900

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 3000 | |
| 196X3000UK (Amps) | | 3000 | |

General Comments:

Replacement Information

ABB Style Number: [196X3000UK](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|-----------|-----------|------------|-------------|--------|-------------|--------------|--------------------|---------|
| 11B803 | 900kV | 26.75 in. | 26.75 in. | 59.5 in. | 102.75 in. | 12 in. | 21 in. | 12 | 1.25 slots in. | 213 in. |
| 196X3000UK | 900kV | 26.75 in. | 26.75 in. | 59.547 in. | 103.297 in. | 12 in. | 21 in. | 12 | 1.25 in. | 216 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|------------|---|------------|-------------------------------|--|
| 11B803 | 79.25 in. | 16.88 in. | N/A | 85.25 in. | 3.0-12 x3.0 | ansi/IEEE fig 3 |
| 196X3000UK | 79.219 in. | 16.875 in. | N/A | 85.234 in. | 3.0-12x4.125, SP x | (8) .500-13UN-2B tapped holes on 6.750 dia B.C. N/A |

Cable Adapter:

NONE

Flange Adapter:

NONE