



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B804
 Voltage Class (kV): 196 BIL (kV): 900

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | 800 | | |
| 196X0800XX (Amps) | 800 | | |

General Comments:

Replacement Information

ABB Style Number: [196X0800XX](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|-----------|-----------|------------|------------|--------|-------------|--------------|--------------------|---------|
| 11B804 | 900kV | 26.75 in. | 26.75 in. | 60 in. | 111.63 in. | 12 in. | 21 in. | 12 | 1.25 slots in. | 230 in. |
| 196X0800XX | 900kV | 26.75 in. | 26.75 in. | 60.046 in. | 111.61 in. | 12 in. | 21 in. | 12 | 1.25 in. | 234 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|------------|------------|---|------------|-------------------------------|--------------------------------------|
| 11B804 | 85.13 in. | 16.875 in. | 101.50 in. | 91.13 in. | 1.5-12 x 2.0 | ansi/IEEE fig 3, 2.0 tube ID |
| 196X0800XX | 85.108 in. | 16.875 in. | 101.531 in. | 91.108 in. | 1.5-12x2.0 x | 2.0 id tube N/A |

Cable Adapter:

NONE

Flange Adapter:

NONE