



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 11B814BB  
**Voltage Class (kV):** 500      **BIL (kV):** 1675

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000CM (Amps)		2000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [550W2000CM](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B814BB	1675kV	24.5 in.	24.5 in.	75.5 in.	207 in.	23 in.	31 in.	16	1.25 in.	360 in.
550W2000CM	1800kV	24 in.	24 in.	75.531 in.	208.315 in.	23 in.	31 in.	16	1.25 in.	450.25 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B814BB	170 in.	23 in.	N/A	177.5 in.	2"-12 X 2.5" USABLE	IEEE fig 3
550W2000CM	170.031 in.	23 in.	N/A	177.531 in.	2.0-12 x 2.50 x	(8) .500 holes 0.750 deep on 6.75 BC N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE