



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B819BB
Voltage Class (kV): 196 **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	1600
196W1620UX (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: [196W1620UX](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Note Difference in "B" dimension - External Buss May Need

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B819BB	900kV	26.75 in.	26.75 in.	59.5 in.	102.44 in.	12.5 in.	21 in.	12	1.25 slots in.	N/A
196W1620UX	900kV	26.75 in.	26.75 in.	59.547 in.	104.861 in.	12 in.	21 in.	12	1.25 in.	216 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B819BB	79.25 in.	16.875 in.	NA in.	85.25 in.	2-12 x 2.625	IEEE fig 3
196W1620UX	79.219 in.	16.875 in.	N/A	85.219 in.	2.0-12x2.625 x 12 UN-2A	IEEE fig 3 (8) .500-13 in.

Cable Adapter: NONE

Flange Adapter: NONE