



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 11B820BB  
**Voltage Class (kV):** 196      **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
196W1620YT (Amps)		1600	2000

**General Comments:**

**Replacement Information**

**ABB Style Number:** [196W1620YT](#) **Alternate ABB Style Number:** [196W1620UX](#)

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Differences in "B" - External Bus May Need Adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B820BB	900kV	26.75 in.	26.75 in.	59.5 in.	102.5 in.	12 in.	21 in.	12	1.25 slots in.	205 in.
196W1620YT	900kV	26.75 in.	26.75 in.	59.547 in.	104.861 in.	12 in.	21 in.	12	1.25 in.	216 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B820BB	79.81 in.	16.875 in.	N/A	85.31 in.	2.0-12 x 2.625	(8) .500-13 x .750 DP on 6.75 BC
196W1620YT	79.219 in.	16.875 in.	N/A	85.219 in.	2.0-12x 2.625, SP x	(8) .500-13UN-2B tapped holes, 6.75 dia B.C. N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE