



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical

**Catalog Number:** 11B823BB

**Voltage Class (kV):** 196      **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		4000	
196W4000UG (Amps)		4000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 196W4000UG **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B823BB	900kV	26.75 in.	26.75 in.	59.5 in.	88.75 in.	12 in.	21 in.	12	1.25 slots in.	173.3 in.
196W4000UG	900kV	26.75 in.	26.75 in.	59.547 in.	88.671 in.	12 in.	21 in.	12	1.25 in.	178 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B823BB	64.63 in.	16.88 in.	N/A	70.63 in.	3.0-12 x 2.875	(8) .5-13 holes on 6.75 bc
196W4000UG	64.593 in.	16.875 in.	N/A	70.593 in.	3.000-12UN-2A, 3.875 USABLE THD, SP x 12 UN-2A	(8) .5-13 holes on 6.75 bc (8) .500-13 in.

**Cable Adapter:**

NONE