



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B828
Voltage Class (kV): 196 **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
230Z0800AA (Amps)	800		

General Comments:

Replacement Information

ABB Style Number: [230Z0800AA](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: See difference in "B" - External Bus may need adjusted. Note Difference in "Tube ID" - Confirm fit of draw lead cable Cable Adapter Required

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B828	900kV	26.75 in.	26.75 in.	60 in.	89.562 in.	12.5 in.	21 in.	12	1.25 in.	170 in.
230Z0800AA	900kV	26.75 in.	26.75 in.	60.046 in.	91.492 in.	9.785 in.	21 in.	12	1.25 in.	208.49 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B828	64.688 in.	16.875 in.	79.44 in.	70.69 in.	1.5-12 x 2.125	2.25 id tube
230Z0800AA	65.406 in.	15 in.	85.042 in.	70.406 in.	1.50-12x2.0, SP x 12 UN-2A	2.0 id tube 2.000 in.I.D. Tube

Cable Adapter: 1ZUA264308-BAA

Flange Adapter: NONE