



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B850BB  
**Voltage Class (kV):** 196      **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
196W1620UB (Amps)		1600	2000

**General Comments:** All Copper Carrying Current Parts

**Replacement Information**

**ABB Style Number:** 196W1620UB **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** All Copper Carrying Current Parts

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B850BB	900kV	26.75 in.	26.75 in.	59.5 in.	90.82 in.	12 in.	21 in.	12	1.25 slots in.	186.75 in.
196W1620UB	900kV	26.75 in.	26.75 in.	59.547 in.	90.765 in.	12 in.	21 in.	12	1.25 in.	178 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B850BB	64.63 in.	16.875 in.	N/A	70.75 in.	2.0-12 x 2.438	(8) .500-13UN-2B, .750 DEEP, EQ SPACED AT 45 DEG, ON 6.750 DIA B.C.
196W1620UB	64.609 in.	16.875 in.	N/A	70.609 in.	2.000-12UN-2A, 2.438 USABLE THD x	(8) .500-13UN-2B, .750 DEEP, EQ SPACED AT 45 DEG, ON 6.750 DIA B.C.