



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B862BB
Voltage Class (kV): 196 **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	2000
196W1620UX (Amps)		1600	2000

General Comments:

Replacement Information

ABB Style Number: [196W1620UX](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" - External Buss May Need Adjusted

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B862BB	900kV	26.75 in.	26.75 in.	59.5 in.	102.44 in.	12 in.	21 in.	12	1.25 in.	215 in.
196W1620UX	900kV	26.75 in.	26.75 in.	59.547 in.	104.861 in.	12 in.	21 in.	12	1.25 in.	216 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B862BB	79.25 in.	16.875 in.	in.	85.25 in.	2-12x2.0	ansi/IEEE fig 3
196W1620UX	79.219 in.	16.875 in.	N/A	85.219 in.	2.0-12x2.625 x 12 UN-2A	IEEE fig 3 (8) .500-13 in.

Cable Adapter: NONE

Flange Adapter: NONE