



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical

**Catalog Number:** 11B869BB

**Voltage Class (kV):** 345      **BIL (kV):** 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
345Z0800BA (Amps)	800		

**General Comments:**

**Replacement Information**

**ABB Style Number:** 345Z0800BA **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Confirm inboard length is acceptable. (See "L" dim.) Cable adapter required to match "CH" dim. Confirm EL and CT lengths are acceptable Note Difference in Tube ID, verify cable fit through conductor tube

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B869BB	1300kV	27 in.	27 in.	55 in.	130.68 in.	15.75 in.	21 in.	12	1.25 in.	257.6 in.
345Z0800BA	1300kV	23 in.	23 in.	51 in.	132.25 in.	11.5 in.	21 in.	12	1.25 in.	369.6 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B869BB	102 in.	16.875 in.	120.6 in.	108 in.	1.5-12x2.00	2.250 id tube
345Z0800BA	102.24 in.	12.75 in.	124.671 in.	108.5 in.	1.5-12x2.125 SP x	2.0 id tube N/A

**Cable Adapter:** P492B596P28