



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B871BB  
**Voltage Class (kV):** 345      **BIL (kV):** 1050

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
345Z0800AA (Amps)	800		

**General Comments:**

**Replacement Information**

**ABB Style Number:** [345Z0800AA](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** See difference in "B" - External Bus may need adjusted. Cable Adapter Required

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B871BB	1050kV	23 in.	23 in.	51 in.	130.7 in.	15.75 in.	21 in.	12	1.25 in.	N/A
345Z0800AA	1175kV	23 in.	23 in.	51 in.	132.25 in.	11.5 in.	21 in.	12	1.25 in.	369.6 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B871BB	102 in.	16.875 in.	120.60 in.	108 in.	1.5-12x2.0	(4) .50-13 holes 6.75 bc 2.0 id tube
345Z0800AA	102.24 in.	12.75 in.	128.86 in.	108.5 in.	1.5-12x2.125 SP x	2.0 id tube N/A

**Cable Adapter:** P492B596P24

**Flange Adapter:** NONE