



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 11B873BB  
**Voltage Class (kV):** 362      **BIL (kV):** 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
362W0800UB (Amps)	800		

**General Comments:**

**Replacement Information**

**ABB Style Number:** [362W0800UB](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Cable Adapter Required.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B873BB	1300kV	23 in.	23 in.	51 in.	133 in.	15.75 in.	21 in.	12	1.25 slots in.	257.6 in.
362W0800UB	1300kV	23 in.	23 in.	51.031 in.	132.656 in.	15.75 in.	21 in.	12	1.25 in.	262.125 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B873BB	102 in.	16.88 in.	122.60 in.	108 in.	1.5-12x2.0	2.0 id tube
362W0800UB	101.984 in.	16.875 in.	126.219 in.	107.984 in.	1.500-12x2.0 x 12 UN-2A	2.0 id tube 2.000 in.I.D. Tube

**Cable Adapter:** 1ZUA264308-BAA

**Flange Adapter:** NONE