



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B874BB
Voltage Class (kV): 345 **BIL (kV):** 1050

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
362W0800UH (Amps)	800		

General Comments:

Replacement Information

ABB Style Number: [362W0800UH](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Cable Adapter Required

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B874BB	1050kV	23 in.	23 in.	51 in.	130.062 in.	15.75 in.	21 in.	12	1.25 in.	250 in.
362W0800UH	1050kV	23 in.	23 in.	51.031 in.	131.656 in.	15.75 in.	21 in.	12	1.25 in.	262.125 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B874BB	102 in.	16.875 in.	120.5 in.	108 in.	2.0-12x2.25	2.0 id tube
362W0800UH	101.984 in.	16.875 in.	126.219 in.	107.984 in.	2.0-12x2.5 x 12 UN-2A	(8) .50-13holes 6.75 bc 2.00 ID TUBE (8) .500-13 in.

Cable Adapter:

1ZUA264308-BAA

Flange Adapter:

NONE