



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**

**Catalog Number:** 11B879BB

**Voltage Class (kV):** 362      **BIL (kV):** 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
345Z2000BD (Amps)		2000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [345Z2000BD](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Difference in "B" - External Bus May Need Adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B879BB	1300kV	23 in.	23 in.	51 in.	128.19 in.	15.75 in.	21 in.	12	1.25 in.	257.6 in.
345Z2000BD	1300kV	23 in.	23 in.	51 in.	131 in.	11.5 in.	21 in.	12	1.25 in.	369.6 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B879BB	102 in.	16.88 in.	N/A	108 in.	2.00-12x2.5, SP	(8).5-13holes x .750 Deep 6.75 bc
345Z2000BD	102.24 in.	12.75 in.	N/A	108.5 in.	2.0-12x3.00 SP x	(8) .500-13 UN-2B on 6.75 BC N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE