



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B887BB
Voltage Class (kV): 550 **BIL (kV):** 1425

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
550Z2000HD (Amps)		2000	

General Comments:

Replacement Information

ABB Style Number: 550Z2000HD **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" - External Buss May Need Adjusted

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B887BB	1425kV	27 in.	27 in.	65 in.	177.81 in.	20 in.	25 in.	12	1.25 slots in.	341 in.
550Z2000HD	1675kV	27 in.	27 in.	65.045 in.	191.392 in.	15 in.	25 in.	12	1.25 in.	562 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B887BB	140.18 in.	20.75 in.	N/A	147.18 in.	2.0-12x2.5	ansi/IEEE fig 3 or IEEE table 7
550Z2000HD	155.188 in.	16.75 in.	N/A	161.5 in.	2.00-12x3.00,SP x	(8) .5-13 holes on 6.75 bc / (4) .500-13 holes on 10.500 bc N/A

Cable Adapter: NONE

Flange Adapter: NONE