



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B888BB
 Voltage Class (kV): 550 BIL (kV): 1550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
550W1600UF (Amps)		1600	

General Comments:

Replacement Information

ABB Style Number: 550W1600UF Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B888BB	1550kV	27 in.	27 in.	65 in.	190.94 in.	20 in.	25 in.	12	1.25 slots in.	362.5 in.
550W1600UF	1550kV	27 in.	27 in.	65.031 in.	191.218 in.	19.969 in.	25 in.	12	1.25 in.	402 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B888BB	153.31 in.	23.625 in.	N/A	160.313 in.	2.0-12x2.5	ansi/IEEE fig 3 or IEEE table 7
550W1600UF	153.156 in	20.75 in.	N/A	160.156 in	2.0-12x3.188 x 12 UN-2A	(8) 5.00-13 tapped holes on 6.75 BC, (4) .500-13 tapped holes on 10.5 BC