



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 11B908BB
Voltage Class (kV): 500 **BIL (kV):** 1425

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000AQ (Amps)		2000	

General Comments:

Replacement Information

ABB Style Number: [550W2000AQ](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Differences in "B" - External Bus May Need Adjusted.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B908BB	1425kV	32 in.	32 in.	90.06 in.	178.4 in.	20 in.	25 in.	12	1.25 in.	N/A
550W2000AQ	1425kV	32 in.	32 in.	90.032 in.	180.136 in.	15 in.	25 in.	12	1.25 in.	515.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B908BB	140 in.	20.75 in.	N/A	147 in.	2.0-12 x 2.5	(8) .5-13 x .938 dp on 6.75 bc
550W2000AQ	144.25 in.	16.000 in.	N/A	150.25 in.	2.000-12x2.50 SP x	(8) .500-13 .750 deep on 6.75 bc N/A

Cable Adapter: NONE

Flange Adapter: NONE