



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B915BB  
**Voltage Class (kV):** 362      **BIL (kV):** 1300

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)	800		
362W0800UD (Amps)	800		

**General Comments:**

**Replacement Information**

**ABB Style Number:** [362W0800UD](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B915BB	1300kV	23 in.	23 in.	51.047 in.	153.36 in.	15.75 in.	21 in.	12	1.25 slots in.	318.13 in.
362W0800UD	1300kV	23 in.	23 in.	51.047 in.	153.171 in.	15.75 in.	21 in.	12	1.25 in.	318.125 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B915BB	122.55 in.	16.88 in.	143.28 in.	128.55 in.	1.5-12 x 2.0	IEEE table 7
362W0800UD	122.484 in.	16.875 in.	143.079 in.	128.484 in.	1.500-12x2.0 x 12 UN - 2A	2.0 id tube 2.000 in.I.D. Tube

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE