



Original Bushing Information

Original Bushing Manufacturer: G.E. Mounting Position:
 Catalog Number: 11B937BB
 Voltage Class (kV): 550 BIL (kV): 1425

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | | 2000 | |
| 550W2000UK (Amps) | | 2000 | |

General Comments:

Replacement Information

ABB Style Number: [550W2000UK](#) Alternate ABB Style Number:

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|--------|--------|--------|------------|-------------|------------|-------------|--------------|--------------------|-------------|
| 11B937BB | 1425kV | 27 in. | 27 in. | 65 in. | 178.63 in. | 20 in. | 25 in. | 12 | 1.25 holes in. | 391 in. |
| 550W2000UK | 1425kV | 27 in. | 27 in. | 65.031 in. | 178.218 in. | 19.969 in. | 25 in. | 12 | 1.25 in. | 425.647 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|-------------|-----------|---|-------------|-------------------------------|---|
| 11B937BB | 140.19 in. | 23.63 in. | N/A | 147.19 in. | 3.0-12 x 2.5 | ansi/IEEE fig 3 (4) 0.5-13x10.5 |
| 550W2000UK | 140.156 in. | 20.75 in. | N/A | 147.156 in. | 2.0-12x3.188 x | (8) .500-13UN-2A tapped holes, 6.75 dia B.C. N/A |

Cable Adapter:

NONE

Flange Adapter:

NONE