



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E. **Mounting Position:** 0-60 degrees

**Catalog Number:** 11B940

**Voltage Class (kV):** 138 **BIL (kV):** 650

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
138W3000UQ (Amps)		3000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 138W3000UQ **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** (A) Note that original bushing had one piece upper porcelain; ABB replacement has multiple piece upper porcelain.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B940	650kV	23 in.	23 in.	46.688 in.	58.312 in.	10.75 in.	15.75 in.	8	1.25 in.	N/A
138W3000UQ	650kV	23 in.	23 in.	46.671 in.	58.048 in.	10.75 in.	15.75 in.	8	1.25 in.	100.5 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B940	42.625 in.	12.125 in.	N/A	48.624 in.	3"-12 x 3.125" usable	IEEE - FIG #3
138W3000UQ	42.641 in.	11.375 in.	N/A	48.641 in.	3.0-12x3.750 x	IEEE fig 3 N/A

**Cable Adapter:** NONE

**Flange Adapter:** NONE