



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:**
Catalog Number: 11B962BB
Voltage Class (kV): 550 **BIL (kV):** 1550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1600	
550W1600UQ (Amps)		1600	

General Comments:

Replacement Information

ABB Style Number: [550W1600UQ](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B962BB	1550kV	27 in.	27 in.	65 in.	190.94 in.	20 in.	25 in.	12	1.25 holes in.	450 in.
550W1600UQ	1550kV	27 in.	27 in.	65 in.	190.938 in.	20 in.	25 in.	12	1.25 in.	450 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B962BB	153.31 in.	20.75 in.	N/A	160.31 in.	2.0-12 x 2.5	ansi/IEEE fig 3 or IEEE table 7
550W1600UQ	153.312 in.	20.75 in.	N/A	160.313 in.	2.0-12 x 2.5 x	IEEE fig 3 N/A

Cable Adapter:

NONE

Flange Adapter:

NONE