



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B981BB  
**Voltage Class (kV):** 196      **BIL (kV):** 900

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		5000	
230W5000UG (Amps)		5000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** [230W5000UG](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B981BB	900kV	26.75 in.	26.75 in.	54.188 in.	94.56 in.	13.5 in.	21 in.	12	1.25 holes in.	176.25 in.
230W5000UG	900kV	26.75 in.	26.75 in.	54.188 in.	94.562 in.	13.5 in.	21 in.	12	1.25 in.	176.25 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B981BB	65.19 in.	N/A	82.50 in.	71.88 in.	4.0-10 x 5.625	ansi/IEEE fig 3
230W5000UG	60.188 in.	16.875 in.	N/A	71.187 in.	4.0-10 x 5.625 x	IEEE fig 3 N/A

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE