



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 11B988BB  
**Voltage Class (kV):** 550      **BIL (kV):** 1550

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
550W2000UE (Amps)		2000	

**General Comments:**

**Replacement Information**

**ABB Style Number:** 550W2000UE **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:**

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
11B988BB	1550kV	27 in.	27 in.	65 in.	190.94 in.	20 in.	25 in.	12	1.25 holes in.	362.5 in.
550W2000UE	1550kV	27 in.	27 in.	65.031 in.	191.218 in.	19.969 in.	25 in.	12	1.25 in.	402 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
11B988BB	153.31 in.	23.625 in.	N/A	160.31 in.	2.0-12x2.5	ansi/IEEE fig 3
550W2000UE	153.156 in.	20.75 in.	N/A	160.156 in.	2.0-12x3.188 x 12 UN-2A	(8) .500-13 on 6.75 BC (4) .500-13 on 10.500 BC (8) .500-13 in.

**Cable Adapter:**

NONE

**Flange Adapter:**

NONE