



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:**  
**Catalog Number:** 157A9950G4  
**Voltage Class (kV):** 15      **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2240	
015J0200AS (Amps)		2000	

**General Comments:** Note difference in amp rating.

**Replacement Information**

**ABB Style Number:** [015J0200AS](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Differences In Minimum Oil Level - "EL", Confirm If Acceptable Replacement bushing has no CT pocket

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
157A9950G4	110kV	18.75 in.	16.5 in.	23.5 in.	10.69 in.	4 in.	7.25 in.	4	.625 in.	N/A
015J0200AS	110kV	16.5 in.	N/A	23.515 in.	11.235 in.	3.734 in.	7.25 in.	4	0.625 in.	14.625 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
157A9950G4	N/A	4.12 in.	N/A	8.19 in.	1.5-12x2.0	1.5-12x2.0
015J0200AS	6.048 in.	4.000 in.	N/A	8.235 in.	1.5-12x2.0 USABLE, SP x 12 UN-2A	1.5-12x2.0 usable 1.500 in.12 UN-2A

**Cable Adapter:** NONE

**Flange Adapter:** NONE