



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 157A9951G01

Voltage Class (kV): 15 **BIL (kV):** 110

| | | | |
|-----------------------|----------|------------------|---------------------|
| Application | DrawLead | Bottom Connected | Oil Circuit Breaker |
| Current Rating (Amps) | 672 | | |
| 015J0060AF (Amps) | 600 | | |

General Comments:

Replacement Information

ABB Style Number: 015J0060AF **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

| Catalog Number | BIL | EL | CT | L | B | D | Bolt Circle | No. Of Holes | Hole Dia. (inches) | Creep |
|----------------|-------|-----------|-----|--------|-----------|----------|-------------|--------------|--------------------|------------|
| 157A9951G01 | 110kV | 19.25 in. | N/A | 20 in. | 11.44 in. | 3 in. | 6 in. | 4 | .625 in. | N/A |
| 015J0060AF | 110kV | 16.5 in. | N/A | 20 in. | 11.5 in. | 3.09 in. | 6 in. | 4 | 0.625 in. | 14.312 in. |

| Catalog Number | Strike | P Dia. | Cable Height/Pin Height for AB Bushing - CH | LHV | Top Terminal Threads (inches) | Bottom Terminal Thread/Configuration |
|----------------|-----------|-----------|---|-----------|--------------------------------|---------------------------------------|
| 157A9951G01 | 8.19 in. | 3.25 in. | 5.94 in. | 8.19 in. | 1.125-12X2.00 | 1.62 i.d. porcelain |
| 015J0060AF | 6.548 in. | 3.250 in. | 6.874 in. | 7.985 in. | 1.125-12x2.000 USABLE, SP x 12 | 1.625 i.d. porcelain 1.562 in.I.D. |

Cable Adapter:

NONE

Flange Adapter:

NONE