



**Original Bushing Information**

**Original Bushing Manufacturer:** G.E.      **Mounting Position:** Vertical  
**Catalog Number:** 157A9951G3  
**Voltage Class (kV):** 15      **BIL (kV):** 110

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1344	
015J0120AP (Amps)		1200	

**General Comments:** Note difference in current rating.

**Replacement Information**

**ABB Style Number:** [015J0120AP](#) **Alternate ABB Style Number:**

**Review dimensional differences verifying critical dimensions to meet application requirements.**

**Notes/Comments:** Note Differences In Minimum Oil Level - "EL", Confirm If Acceptable

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
157A9951G3	110kV	19.25 in.	16.5 in.	23.25 in.	11.44 in.	3 in.	6 in.	4	.625 in.	N/A
015J0120AP	110kV	16.5 in.	N/A	23 in.	11.5 in.	3.09 in.	6 in.	4	0.625 in.	14.312 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
157A9951G3	6.75 in.	3.25 in.	N/A	8.19 in.	1.125"-12 x 2" usable	1.125"-12 x 2.5" usable
015J0120AP	6.813 in.	3.250 in.	N/A	8.25 in.	1.125-12x2.0, SP x 12 UN-2A	1.125-12x2.5 1.125 in.12 UN-2A

**Cable Adapter:** NONE

**Flange Adapter:** NONE