



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical

Catalog Number: 15B135

Voltage Class (kV): 46 **BIL (kV):** 250

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		2000	
046W2000UL (Amps)		2000	

General Comments:

Replacement Information

ABB Style Number: [046W2000UL](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Note Difference in "B" - External Buss May Need Adjusted

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B135	250kV	21 in.	21 in.	34.5 in.	26 in.	5.25 in.	9.25 in.	6	.875 in.	N/A
046W2000UL	250kV	21 in.	21 in.	34.5 in.	37 in.	5.15 in.	9.25 in.	6	0.875 in.	56.906 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B135	18.625 in.	5.875 in.	N/A	20.375 in.	2"-12 X 2.938" LG; SP	2"-12 X 2.625" LG
046W2000UL	24.548 in.	5.75 in.	N/A	27.548 in.	2.000-12UN-2A, 2.625 USABLE THD, SP x	2.000-12UN-2A 3.922 USABLE THD N/A

Cable Adapter: NONE

Flange Adapter: NONE