



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 15B14
Voltage Class (kV): 23 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		1200	
025W0412AT (Amps)	400	1200	1200

General Comments:

Replacement Information

ABB Style Number: [025W0412AT](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: Check "B" Dimension, External Buss May Need Adjustment. Check "L" Dimension, Confirm If Acceptable

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B14	150kV	21 in.	21 in.	30.5 in.	15.13 in.	3.13 in.	7.25 in.	4	.875 slots in.	N/A
025W0412AT	150kV	21 in.	21 in.	29.531 in.	20.781 in.	3.219 in.	7.25 in.	4	0.875 in.	21 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B14	9.19 in.	4 in.	N/A	10.94 in.	1.5 - 12 x 2.125	1.5 - 12 x 2.19
025W0412AT	10.687 in.	3.5 in.	16.282 in.	12.437 in.	1.5-12X2.25 usable, SP x 12 UN - 2A	1.5-12x2.25 usable, .875 id tube .875 in.

Cable Adapter: NONE

Flange Adapter: NONE