



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 15B148
Voltage Class (kV): 23 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
025W3000BF (Amps)		3000	

General Comments:

Replacement Information

ABB Style Number: 025W3000BF **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments:

Note Difference In "B" - External Buss May Need Adjustment

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B148	150kV	21 in.	21 in.	34.3 in.	16.94 in.	5.25 in.	9.25 in.	6	0.875 in.	N/A
025W3000BF	150kV	21 in.	21 in.	34.312 in.	22.422 in.	4.699 in.	9.25 in.	6	0.875 in.	21.875 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B148	9.125 in.	6 in.	NA in.	10.875 in.	3.0-12 x 3.25 SP	(2) .688 hole pad 1.75 centersw
025W3000BF	12.297 in.	5.75 in.	N/A	15.297 in.	3.0-12x3.125, SP x 12 UN-2A	(2) .688 hole blade .688 dia in.

Cable Adapter: NONE

Flange Adapter: NONE