



Original Bushing Information

Original Bushing Manufacturer: G.E. **Mounting Position:** Vertical
Catalog Number: 15B151BB
Voltage Class (kV): 25 **BIL (kV):** 150

Application	DrawLead	Bottom Connected	Oil Circuit Breaker
Current Rating (Amps)		3000	
025W3000LT (Amps)		3000	

General Comments: This bushing can be mounted 0 - 90 degrees from vertical.

Replacement Information

ABB Style Number: [025W3000LT](#) **Alternate ABB Style Number:**

Review dimensional differences verifying critical dimensions to meet application requirements.

Notes/Comments: This bushing can only be mounted 0 -60 degrees from vertical. Note Difference In "B" Dimension, External Buss May Need Adjustment. Note New Bottom Terminal Connector May Be Required.

Catalog Number	BIL	EL	CT	L	B	D	Bolt Circle	No. Of Holes	Hole Dia. (inches)	Creep
15B151BB	150kV	21 in.	21 in.	32.375 in.	16.94 in.	5.25 in.	9.25 in.	6	.875 in.	N/A
025W3000LT	150kV	21 in.	21 in.	32.375 in.	22.203 in.	4.699 in.	9.25 in.	6	0.875 in.	21.875 in.

Catalog Number	Strike	P Dia.	Cable Height/Pin Height for AB Bushing - CH	LHV	Top Terminal Threads (inches)	Bottom Terminal Thread/Configuration
15B151BB	9.125 in.	5.875 in.	N/A	12.565 in.	3.0-12x3.25, SP	(4) .562 hole blade spaced 1.75 x 1.25
025W3000LT	12.078 in.	5.75 in.	N/A	15.078 in.	3.0-12x3.125, SP x	(2) .688 hole blade, 4.188 x 2.375 x 0.75 N/A

Cable Adapter: NONE